

Nodo

oasis



ALL THE DIRT

Fabrication & Material

One-piece, rotationally-molded, specially formulated, LLDPE, low-density polyethylene. Material thickness 3.8 mm. UV Treatment, -100 C to 65 C heat resistant,

Warranty

Rotational casting components for a 2-years period and the other components for a 1-year period against any defect in material or manufacturing.

Maintenance

For routine and regular cleaning maintenance, Oasis recommends the use of Simple Green® or an equivalent cleaning product. This product is bleach/water solution cleanable and suitable for use with hospital-grade disinfectants (such as Virex®, Wexcide® or Oxivir Five 16®) per manufacturers' instructions.

Performance Test Standards

Product tested to 500 lbs (226.8 kg) static load.

Environmental

Our plastic materials are entirely recyclable. Our products in black color are made of 100% recycled resin. Our manufacturing process, rotational molding, does not produce any plastic waste.

Flammability

Our resin has UL 94 HB (f1) certification : flammability rating for materials that have passed both the UL 94 horizontal burning (HB) test and a specific UL outdoor weatherability (f1) test. The HB rating means the material burns slowly in a horizontal position and stops before burning through 125 mm, with specific burning rate limits depending on its thickness. The (f1) rating indicates the material has also passed outdoor weatherability testing, including UV exposure and water immersion, and retains its flammability properties after exposure.

Ballasting: Can be weighted with dry sand or gravel onsite. Ballast material not supplied by Oasis

Model:	OS.DI.100			
Weight	3	kg	6.6	lbs
Width	35.6	cm	14	in
Depth	35.6	cm	14	in
Height	45.7	cm	18	in

18	13	50
20	28	51
30	36	
39	66	
42	72	
82	79	
29	85	
98	97	

Made in
Canada

